

# **Parallax**

### **Bathroom Vanity & Sconce**

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-73118 18"	2700K/3000K/3500K	BK Black BN Brushed Nickel CH Chrome	6W	271	189

Example: WS-73118-CH

For custom requests please contact customs@waclighting.com

### DESCRIPTION

Straight forward and honest. Unparalleled

### **FEATURES**

- Fontlight illumination
- Conversion plate included to accommodate 4" junction box
- 3CCT (2700K/3000K/3500K) selectable switch
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Option to pre-select color temperature or adjust in the field
- ACLED driverless technology
- 5 year warranty

### **SPECIFICATIONS**

 Color Temp:
 2700K/3000K/3500K

 Input:
 120 VAC,50/60Hz

**CRI:** 90

**Dimming:** ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL, Title 24 JA8 Compliant

Damp Location Listed

Construction: Aluminum body, PC diffuser




### **FINISHES:**



Nickel

### LINE DRAWING:



WS-73118

# WAC LIGHTING

# **Parallax**

## **Bathroom Vanity & Sconce**

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-73124 24"	2700K/3000K/3500K	BK Black BN Brushed Nickel CH Chrome	6W	393	295

Example: WS-73124-CH

For custom requests please contact customs@waclighting.com

### DESCRIPTION

Straight forward and honest. Unparalleled

### **FEATURES**

- Fontlight illumination
- Conversion plate included to accommodate 4" junction box
- 3CCT (2700K/3000K/3500K) selectable switch
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Option to pre-select color temperature or adjust in the field
- ACLED driverless technology
- 5 year warranty

### **SPECIFICATIONS**

 Color Temp:
 2700K/3000K/3500K

 Input:
 120 VAC,50/60Hz

**CRI:** 90

**Dimming:** ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,Title 24 JA8 Compliant

Damp Location Listed


Construction: Aluminum body, PC diffuser



### **FINISHES:**



### LINE DRAWING:



WS-73124