

Spectre

Bathroom Vanity & Sconce

_

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-93120 20"	2700K/3000K/3500K	BK Brushed Black BN Brushed Nickel	17W	1731	752

Example: WS-93120-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

One moment there, gone the next. Sublime luminous spirit.

FEATURES

- Slim cutting-edge light guide material
- Can be mounted with or without canopy (slim junction JB-0501 box sold separately)
- Conversion plate included to accommodate 4" junction box
- 3CCT (2700K/3000K/3500K) selectable switch
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Option to pre-select color temperature or adjust in the field
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 60000 Hours

Mounting: Can be mounted on ceiling or wall in all orientations

Standards: ETL, cETL

Damp Location Listed

Construction: Aluminum body, light guide material diffuser




FINISHES:



Nickel Black

LINE DRAWING:





WS-93120

WAC LIGHTING

Spectre

Bathroom Vanity & Sconce

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-93127 27"	2700K/3000K/3500K	BK Brushed Black BN Brushed Nickel	23W	2295	1060

Example: WS-93127-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

One moment there, gone the next. Sublime luminous spirit.

FEATURES

- Slim cutting-edge light guide material
- Can be mounted with or without canopy (slim junction JB-0501 box sold separately)
- Conversion plate included to accommodate 4" junction box
- 3CCT (2700K/3000K/3500K) selectable switch
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Option to pre-select color temperature or adjust in the field
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 60000 Hours

Mounting: Can be mounted on ceiling or wall in all orientations

Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum body, light guide material diffuser



FINISHES:



LINE DRAWING:



WS-93127